

Triton® II

Fiberglass Sand Filter

By Pentair Pool Products®



The #1 sand filter in the world

Triton® II is the result of over 40 years of product evolution and refinement. It has set the industry standard for effectiveness, efficiency, long runs between service, and providing years of dependable, low maintenance operation.

Triton II features a special internal design that keeps the sand bed level, ensuring even water flow, and resulting in the most efficient filtration possible.

- Time-proven internal design ensures that all water receives maximum filtration for crystal clear results.
- GlasLok™ process creates a one-piece, fiberglass reinforced tank with a UV-resistant coating for years of dependable, corrosion-resistant service.
- Flow system design controls filtration quality and ensures maximum run times between backwashing to save you time.



Triton® II Fiberglass Sand Filter



Easy access, heavy-duty closure with built-in pressure relief valve makes inspection and maintenance fast, safe, and easy

Threaded bulkhead connectors for easy installation and service

GlasLok™ process creates a one-piece, fiberglass reinforced tank with UV-resistant surface finish for years of unequal strength and durability

Model Number	Filter Area Sq. Ft.	Vertical* Clearance	Filter Diameter	Required Sand† (lbs)	Flow Rate GPM		Turnover Capacity-Res. (Gallons)		
					Res.**	Com.	8hrs.	10hrs.	12hrs.
TR 40	1.92	32.5"	19"	175	38	38	18,240	22,800	27,360
TR 50	2.46	36.75"	21"	225	49	49	23,520	29,400	35,280
TR 60	3.14	37.5"	24"	325	63	63	30,240	37,800	45,360
TR 100	4.91	41.75"	30"	600	98	74	47,040	58,800	70,560
TR 140	7.06	47.25"	36"	925	141	106	67,680	84,600	101,520

† Use standard #20 silica sand.
 * Required clearance to remove the closure.
 ** Maximum flow rate. Flow rate is based on 20 GPM per sq. ft. of filter area. Actual system flow will depend on plumbing size and other system components.

The best reputation in the industry for all the right reasons

Besides its superior filtration performance, Triton® II delivers a level of dependability and ease of operation and maintenance for a track record that's unsurpassed. Every design detail has been refined to make Triton II the industry standard. Additional features include:

- Combination sand and water drain speeds servicing and winterizing.
- All internal parts are threaded for ease of maintenance.
- Swing-away water diffuser allows instant access to sand and all internal parts.
- One-year limited warranty. See warranty for details.

Available from:



Because **reliability** matters most®

www.pentairpool.com

Phone: 800-831-7133 Fax: 800-284-4151

pumps / filters / heaters / heat pumps / automation / lighting / cleaners / sanitizers / maintenance products

